



Array Grout | Sanded Acrylic Grout

- Pre-mixed, ready-to-use grout
- Stain, mold and mildew resistant
- For grout joints from 1/16" to 3/16"
- Can be used with: luxury vinyl plank & tile, ceramic and porcelain

DESCRIPTION

Array Grout is a sanded acrylic grout. The sanded feature gives the grout a beautiful texture and enhances its durability under foot. The acrylic feature makes the grout flexible, which helps eliminate separation cracks and fall-

out. Non-acrylic grouts tend to crack over a period of time and use due to the shifting of the subfloor. Array Grout eliminates the need for epoxy grouts, which are expensive and difficult to install.

AVAILABLE GROUT CHOICES



COMPARE TO

Armstrong S-693 Sanded Acrylic Grout (fo Alterna), Mannington Adura Grout, Congoleum Duraceramic Premixed Grout, Metroflor Tru-Grout, Mapei Luxury Vinyl Tile Grout, Precision Components Pre-Mixed Grout for LVT

SPECIFICATIONS		
Description	Premixed sanded, acrylic grout.	
Unit Size	1 gallon	
Use	For grouting joints 1/16" to 1/4" wide.	
Limitations	Not recommended for exterior use, shower floors or underwater use.	
Coverage	Joint Width	Approximate Coverage 16" x 16" Tile
	1/16" (1.6mm)	450 sq. ft./gal. (42m ²)
	1/8" (3.2mm)	325 sq. ft./gal. (31m ²)
	3/16" (4.8mm)	275 sq. ft./gal. (26m ²)
	1/4"(6.4mm)	225 sq. ft./gal. (21m ²)
Applicator	Hard rubber float or green epoxy float.	
	Cleanup with firm sponge and 3M® white pad.	
Working Time	10 minutes - for best results apply grout in a 6-10 sq. ft. area on floors and clean-up immediately.	
Set up Time	8 hours	
Cleaning	Wet - Water	
	Dry - Household ammonia cleaner.	
	Do not use grout haze removers.	
Tracers	N/A	
Shelf Life	1 year if unopened	
Freeze/Thaw Stability	Yes	
Flammable	No	
Cautions	Potential skin, eye and respiratory irritant	