



**Shaw Cork Underlayment 165BA** 3 mm (approx. 1/8")  
48" x 50' / 200 s.f./roll

**200BM** 6 mm (approx. 1/4")  
48" x 50' / 200 s.f./roll

**167BA** 6mm (approx. 1/4")  
48" x 25' / 100 s.f./roll

- Impact sound control
- Use with hardwood, laminate, ceramic & natural stone
- 100% natural & sustainable cork
- Non-toxic & hypoallergenic
- Naturally resistant to mold & mildew

## SOUND RATINGS FOR SHAW CORK UNDERLAYMENT:

### Floor/Ceiling Assemblies

	Test Reference	Subfloor	Product/ Thickness	Suspended Ceiling	Overlay	Floor Covering	Sound Ratings	
							IIC	STC
<b>Wood Joist Floor Systems</b> (2x10 Sawn Joists 5/8 Wallboard-RC1)	RAL IN95-11•RAL TL95-118	5/8" Plywood	6mm	Yes	1 1/2" Gypsum concrete	Ceramic Tile	<b>57</b>	<b>60</b>
	RAL IN95-19•RAL TL95-126	5/8" Plywood	6mm	Yes	1 1/2" Gypsum concrete	Parquet Wood	<b>54</b>	<b>59</b>
	RAL IN95-15•RAL TL95-122	5/8" Plywood	6mm	Yes	1 1/2" Gypsum concrete	Laminate Floor	<b>53</b>	<b>60</b>
	RAL IN98-37•RAL TL98-186	5/8" Plywood	6mm	Yes	1 1/2" Gypsum concrete	Floating Wood	<b>57</b>	<b>60</b>
	RAL IN94-20•RAL TL94-296	5/8" Plywood	6mm	Yes	1 1/2" Mortar Bed	Ceramic Tile	<b>50</b>	<b>61</b>
	RAL IN94-19•RAL TL94-274	5/8" Plywood	6mm	Yes	1/2" Cement Backer Board	Ceramic Tile	<b>50</b>	<b>64</b>
<b>Concrete Floor Systems</b>	RAL IN95-3•RAL TL95-256	4" Slab	6mm	Yes	1 1/2" Mortar Bed	Ceramic Tile	<b>59</b>	<b>60</b>
	RAL IN95-37•RAL TL95-256	6" Slab	6mm	Yes	<b>None</b>	Ceramic Tile	<b>61</b>	<b>60</b>
	RAL IN95-43•RAL TL95-366	6" Slab	6mm	Yes	<b>None</b>	Glued Wood	<b>61</b>	<b>62</b>
	RAL IN95-42•RAL TL95-365	6" Slab	6mm	Yes	3/4" Plywood	Nailed Wood	<b>61</b>	<b>61</b>
	RAL IN95-41•RAL TL95-364	6" Slab	6mm	Yes	<b>None</b>	Floating Wood	<b>63</b>	<b>60</b>
	RAL IN95-2•RAL TL95-40	6" Slab	6mm	Yes	1/2" Cement Backer Board	Ceramic Tile	<b>60</b>	<b>60</b>
	RAL IN98-4•RAL TL98-27	6" Slab	6mm	<b>No</b>	<b>None</b>	Floating Wood	<b>50</b>	<b>52</b>